



Elbow 90° PVC-U Rp

Model:

- With parallel female thread Rp
- Connection to plastic thread only
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

Thread Type	Size (inch)	PN (bar)	Code	SP	Weight (kg)	z (mm)	D (mm)	L (mm)
Rp	3/8	10	721 101 605	10	0.013	9	23	23
Rp	1/2	10	721 101 606	10	0.017	12	27	27
Rp	3/4	10	721 101 607	10	0.029	15	33	33
Rp	1	10	721 101 608	10	0.042	19	39	39
Rp	1 1/4	10	721 101 609	10	0.070	27	48	49
Rp	1 1/2	10	721 101 610	5	0.178	35	61	59
Rp	2	10	721 101 611	5	0.322	44	75	72

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>