



Adaptor socket PVC-U BS Inch Rp



Model:

- With solvent cement socket BS Inch and parallel female thread Rp
- Do not use thread sealing pastes that are harmful to PVC-U
- Install with low mechanical stress and avoid large cyclic temperature changes
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads



Thread Type	Size (inch)	PN (bar)	d (inch)	Code	SP	Weight (kg)	z (mm)	L (mm)	s (mm)
Rp		15	$\frac{3}{8}$	721 911 005	10	0.016	4	31	27
Rp		15	$\frac{1}{2}$	721 911 006	10	0.024	4	35	32
Rp	$\frac{3}{4}$	15	$\frac{3}{4}$	721 911 007	10	0.030	3	40	36
Rp	1	15	1	721 911 008	10	0.055	3	45	46
Rp	1 $\frac{1}{4}$	15	1 $\frac{1}{4}$	721 911 009	10	0.083	3	51	55
Rp	1 $\frac{1}{2}$	15	1 $\frac{1}{2}$	721 911 010	10	0.127	8	59	65
Rp	2	15	2	721 911 011	5	0.215	8	69	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>