



## Reducing bush PVC-U R Rp

### Model:

- With taper male thread R and parallel female thread Rp
- Connection to plastic threads only
- Do not use thread sealing pastes that are harmful to PVC-U
- Install with low mechanical stress and avoid large cyclic temperature changes

R	Rp	PN	code	SP	weight	z	L	s	
[inch]	[inch]	[bar]			[kg]	[mm]	[mm]	[mm]	
1/2	3/8	10	<b>721 910 834</b>	10	0.014	25	36	27	
3/4	1/2	10	<b>721 910 837</b>	10	0.021	25	39	32	
1	1/2	10	<b>721 910 842</b>	10	0.029	31	45	32	
1	3/4	10	<b>721 910 841</b>	10	0.031	29	45	36	
1 1/4	1	10	<b>721 910 846</b>	10	0.050	32	50	46	
1 1/2	1 1/4	10	<b>721 910 852</b>	10	0.065	35	55	55	
2	1 1/2	10	<b>721 910 858</b>	5	0.127	45	65	65	

The technical data are not binding and not expressly warranted characteristics of the goods. They are subject to change. Our General Conditions of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.piping.georgfischer.com>